題號: 255 科目: 熱工學

節次: 8 共2頁之第1頁

題號:255

Air is treated as an ideal gas (molecular weight 28.97 kg/kmol, thermal conductivity 0.025 W/m·K, specific heat 1.025 kJ/kg·K), the emissivity of stainless steel = 0.7, the universal gas constant = 8.314 kJ/kmol·K, Stefan-Boltzmann constant =  $5.67 \times 10^{-8} \text{ W/m}^2 \cdot \text{K}^4$  and  $0^{\circ}\text{C} = 273.15 \text{ K}$ .

- 1. Air at 400 K and 0.5 bar is initially in a well-insulated and rigid vessel that has a volume of 2 m³. After another air at 450 K and 1.5 bar flows into the vessel, the finial temperature of air in the vessel is 500 K. Please determine (a) the initial mass of air in the vessel, in kg, (b) the total mass of air flowing into the vessel, in kg, (c) the finial vessel pressure, in bar, and (d) the entropy production after this thermodynamic process, in kJ/K. (40%)
- 2. A household dehumidifier steadily operates in an ambience of 1 bar, 30°C and 95% relative humidity, where 10% of its electrical power as heat loses to the surroundings. The inlet flow rate of the dehumidifier is twelve tons per day. The air flow leaves the outlet at 35°C and 1.05 bar accompanied by a condensate flow rate of 10 kg/day at 15°C. Please determine (a) the mass flow rate of water vapor at the inlet, in kg/day, (b) the relative humidity of exiting air, and (c) the power required to operate the dehumidifier, in W. (30%)
- 3. In a hot rolling process, a 6m-long cylinder of stainless steel (180 mm in diameter) is heated by an induction heater to obtain a uniform temperature at 1200°C after leaving the preheating furnace. The induction heater steadily operates at 1 MW, where its energy efficiency is 65.36%. The ambient air is estimated at 50°C. Please determine (a) the heat transfer coefficient of the cylinder, in W/m²·K, and (b) the heat flux ratio of convection to radiation of the cylinder. (20%)
- 4. The virial form expressing the p-v-T relation of air is given as follows:

$$p = \frac{RT}{v} + \frac{a}{v^2} + \frac{b}{v^3} + \frac{c}{v^4}$$

where R is the gas constant, (a, b, c) are equation constants, and (p, T, v) denotes pressure, temperature and specific volume, respectively.

If the compressibility factor of air at the critical point is  $\frac{2}{7}$ , please

determine the value of 
$$\frac{\sqrt{ac}}{b}$$
. (10%)

題號: 255

國立臺灣大學 108 學年度碩士班招生考試試題

題號:255

共2頁之第2頁

<b>严助</b>	<i>2</i> 00		西亚里冯八寸	- 100	7 1 1	· <del>从</del> 二 ~
科目:	熱工學					

節次: 8		•									天 2	真之第	* Z
Properties of Sat			: Volume /kg	Internal I		l	Enthalpy kJ/kg	ngkiri kilifa dindundi de sagunir belar safiilikadibi	Entr kJ/kg		<del> </del>		
(Liquid-V	Temp. Press		Sat, Vapor	Sat. Liquid	Sat. Vapor	Sat. Liquid	Evap.	Sat. Vapor	Sat. Liquid	Sat. Vapor	Tem		
	°C bar	$v_{\rm f} \times 10^3$ $1 - 1.0002$	v <sub>g</sub> 206.136	u <sub>t</sub>	u <sub>s</sub> 2375 3	h <sub>t</sub>	h <sub>fg</sub>	h <sub>g</sub> 2501.4 ↔	0.0000	9,1562	°C ∵01≀		
	4 0:008 5 0:008	3 1.0001	157.232 147.120		2380.9 2382.3	16.78 4 20.98 5		2508:7 2510:6	0.0610 0.0761	9.0514 9:0257:	4 5	•	
	6 0.009 8 0.010	5 1,0001	137.734 120.917	25.19 33.59	2383.6 2386.4	25.20 33.60	2487.2	2512.4 2516.1	0.0912 0.1212	9.0003 8:9501	. 6 8		
	10 0.0123	28 1.0004	106.379	42.00	2389.2	42.01	2477.7	2519.8	0.1510	8.9008	10		
	11 0.0131 12 0.0140	02   1.0005	99.857 93.784	46.20 50.41	2390.5 2391.9	46.20 50.41	2475.4 2473.0	2521.6 2523.4	0.1658 0.1806	8.8765 8.8524	11 12		
	13 0.0149 14 0.0159		88.124 82.848	54.60 58.79	2393.3 2394.7	54.60 58.80	2470.7 2468.3	2525.3 2527.1	0.1953 0.2099	8.8285 8.8048	13 14		
	15 0.0170 16 0.018		77.926 73.333	62.99 67718	-2396,1 -2397'4	62.99 67:19	2465.9 2463.6	2528.9 2530.8	0,2245 0.2390	8.7814 8.7582	15 16		
	17 0.019 18 0.020	1.0012	69:044 65:038	71.3 <b>8</b> 73.57	2398.8 2400.2	71.38 75.58	2461.2 2458.8	2532.6 2534.4	0.2535 0.2679	8.7351 8.7123	17 18		
	19 0.021	1.0016	61.293	79.76	2401.6	79:77	2456,5	2536.2	0.2823	8.6897	19		
	20 0.0233 21 0.0244	37 1.0020	57.791 54.514	83.95 88.14	2402.9 2404.3	83.96 88.14	2454.1 2451.8	2538.1 2539.9	0.2966	8.6672 8.6450	20 <sup>-</sup> 21		
	22 0.0264 23 0.028		51.447 48.574	92.32 96.51	2405.7 2407.0	92.33 96.52	2449.4 2447.0	2541.7 2543.5	0.3251	8.6229 8.6011	22 23		
	24 0.0298 25 0.031	1	45.883 - 43.360	100.70 104.88	2408.4 2409.8	100.70 104.89	2444.7 2442.3	2545.4 2547.2	0.3534	8.5794 8.5580	24 25.		
	26 0.033	1:0032	40.994	109.06	2411,1	109.07	2499,9	2549.0 2550.8	0.3814 0.3954	8:5367	26. 27		
	27 0.035 28 0.037	1.0037	38.774 36.690	113.25 117.42	2413.9	313.25 137.43	2437.6 2435.2	2552.6	0.4093	8.5156 8.4946	.28		
	29 0.040 30 0.042		34,733 32.894	125.78	2415.2 2416.6	121,61 125.79	2432.8 4 2430.5	2554.5 · 2556.3	0.4231	8.4739 8.4533	29 30		
	31 0.044 32 0.047	96 1.0046	31.165 29.540	129.96 134.14	2418.0 2419.3	129.97 134.15	2428.1 2425.7	2558.1 2559.9	0.4507 0.4644	8.4329 8.4127	31 32		•
	33 0.050 34 0.053	34 1.0053	28.011 26.571	138.32 142.50	2420.7 2422.0	138.33 142.50	2423.4 2421.0	2561.7 2563.5	0.4781	8.3927 8.3728	33 34		
	35 0.056	28 1,0060	25.216	146.67	2423.4	146.68	2418.6	2565,3	0.5053	8.3531	ı 35		
	36 0:059 38 0.066	32 1.0071	23.940 21.602	150.85 159.20	2424.7. 2427.4	150.86 159.21	2416.2 2411.5	2567.1 2570.7	0.5188	8,3336 8,2950	36 38		
	40 0.073 45 0.095	84 1,0078 93 1.0099	15.258	188.44	2436.8	188.45	2394.8	2583,2	0.6387	8:1648	45		
dea Gas Proper	rties of Air		<del></del>	(K), $h$ and $u$ on $\Delta s = 0^1$	(kJ/kg), s°	(kJ/kg·K)		w. eur eur terrenten	,	when $\Delta s =$	0		
	T h	u s°		$v_{\rm r}$	T	· h	и	s°			v,		
	200 199.97 210 209.97	142.56 1.295 149.69 1.344			450 460					5,775 22. 6,245 21			
	220 219.97 230 230.02	156.82 1.391 164.00 1:435	0.469	0 1346.	470 480			2 2,156 0 2,177	04	6.742 200 7.268 189	0.1 9.5		
	240 240.02	171.13 1.478	324 0.635	5 1084.	490	492.74	352.0	8 2.198	76	7.824 179	9.7		
	250 250.05 260 260.09	178.28 1.519 185.45 1.558	348 0.840	5 887.8	1	513.32	366.9	2.239	93		2.1		,
	270 270.11 280 280.13	192.60 1.596 199.75 1.632	279 1.088	738.0		533.98	381.8	4 2.279	67 1		6.7		
	285 285.14 290 290.16	203.33 1.650 206.91 1.668	I .						- 1	1,10 13 1,86 13	9.7 3:1		
	295 295.17 300 300.19	210.49 1.68 214.07 1.70	515 1.306	8 647.9	560	565,17	404.4	2 2.336	85 1	2.66 12	7.0 1.2		
	305 305.22 310 310.24	217.67 1.711 221.25 1.73	B65 1.468	596.0	580	586.04	419.5	5 2,373	48 1	4.38 . 11	5.7 0.6		
	315 315.27	224.85 1.75	106 1.644	12 549.8	600	607.02	434.7	8 2.409	002 1	6.28 10	5.8		
	320 320.29 325 325.31	228.42 1.766 232.02 1.78			1		450.0	9 2.443	356 1	8.36 9	1.2 6.92		
	330 330.34 340 340.42	235.61 1.79° 242.82 1.82°									2.84 8.99		<b>.</b>
	350 350.49	250.02 1.85	708 2.379	9 422,2				5 2,493 1 2,509			5,34 1:89		は、見
	360 360.58 370 370.67	257.24 1.88 264.46 1.91	313 2.89	2 367.2	670	681,14	488.8	1 2.525	i <b>89.</b> - 2	4.46 7	8.61		
	380 380.77 390 390.88	271.69 1.94 278.93 1.96				war and the second seco		2 2,54 5 2,55			5,50 2,56		子
	400 400.98 410 411.12	286.16 1.99 293.43 2.01									9.76 7.07		言是 瞪光線
	420 421.26 430 431.43	300.69 2.04 307.99 2.06	142 4.52	2 266.6	720	734.82	528.1	4 2.603	319 3	32.02 6	4.53 2.13		回
	440 441.61	315.30 2.08									9.82		